Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# MATERIAL SAFETY DATA SHEET BLIXEM WINDSCREEN WASHER

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: BLIXEM WINDCREEN WASHER

**Product Details:** Liquid **Manufacturer/Supplier** OILFLOW cc

4 Saligna Street, Boksburg, Johannesburg, South Africa 1459

Health Emergency Telephone 011 827 5848

Oilflow Website: info@oilflow.co.za

Www.oilflow.co.za

#### 2. HAZARD IDENTIFICATION

#### Classification

Flammable liquid and Vapour. Causes serious eye irritation. Toxic if inhaled.

#### Labelling

Hazard designation: F - Flammable



Dangers for humans and environment: Flammable liquid. In use, keep hands and product away from all naked flame. (R10).

Hi



Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# MATERIAL SAFETY DATA SHEET BLIXEM WINDSCREEN WASHER

### 3. COMPOSITION/INFORMATION ON THE COMPONENTS

**Description**: Mixture of following substances and cleaning components.

**Components in Product** 

Component Name Concentration (%)

 Alcohol
 3-5

 NP 9
 3-10

 Acetic acid
 1 - 4

 Water
 20 - 90

#### 4. FIRST AID MEASURES AND RESPONSE

Eyes: If splashed on eyes, hold the eyelids apart and pass running water for 15 minutes (S26).

If irritation occurs, contact the physician, and have product or label at hand. (P101)

Skin: If skin contact occurs, remove contaminated clothing and pass running water to affected

skin.

Ingestion: If swallowed, do not induce vomiting, rinse mouth and give water to sip, if vomiting persists,

bend head closer to hips to avoid vomitus entry into lungs.

Seek medical advice immediately and show this MSDS (R22) (S46).

Inhalation: Retreat to get fresh air immediately. Seek medical attention if rapid recovery does not occur.

### 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing media: High volume water jet

Specific hazards

during firefighting: Do not use a solid water stream as it may scatter and spread fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion products: Carbon oxides

Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do so.

Evacuate area.

Special protective equipment

for fire-fighters: In the event of fire, wear self-contained breathing apparatus. Use personal



Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# **MATERIAL SAFETY DATA SHEET BLIXEM WINDSCREEN WASHER**

#### 6. ACCIDENTAL RELEASE MEASURES

Person-related safety precautions: Avoid contact with eyes (S25).

Ensure adequate ventilation (S51).

Keep away from sources of ignition (S16).

When using, do not smoke (S21)

Measures for environmental protection:

Prevent undiluted product from reaching sewage system. Measures for cleaning / collecting: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust) and dispose according to local

regulations.

#### 7. HANDLING AND STORAGE

Advice on safe handling: Do not breathe vapours or spray mist.

Keep out of reach of children (S02)

Do not swallow. Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety

practice.

Non-sparking tools should be used. Keep container tightly closed (S07).

Keep away from heat and sources of ignition (S16). Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage: Keep in properly labelled containers.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the national regulations. Keep away from heat and sources of ignition.

Do not store in direct sunlight.

Materials to avoid: Do not store with the following product types:

Strong oxidizing agents

Organic peroxides Flammable solids

Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases **Explosives Gases** 





Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# MATERIAL SAFETY DATA SHEET BLIXEM WINDSCREEN WASHER

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection Avoid eye contact. The wearing of chemical safety goggles or face

shield is recommended.

Skin and body protection Avoid contact with skin or clothing. Skin contact can be minimized

by wearing impervious protective clothing including gloves. Protective clothing made from neoprene, nitrile, or n-butyl rubber

is suitable in these applications.

Respiratory protection None Required. However, an approved respirator is

recommended if operating conditions generate vapour, mists or fumes, and if exposure cannot adequately be controlled by local exhaust ventilation. Wear approved respiratory protection such

as a toxic dust, mist and fume respirator.

Hand Protection Gloves suitable for permanent contact:

No hand protection required under normal conditions:

Ventilation No special ventilation is usually necessary. However, if operating

conditions create high airborne concentrations of this material, engineering controls may be needed. Local exhaust ventilation and/or enclosure of the process is preferred in these cases.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid

Colour Clear or colourant may be used as when required.

Odour Alcoholic odour

pH Neat @20°C  $8 \pm 0.5$ Boiling Range/Point (°C) 78 - 100Flash Point (PMCC) (°C) 40

Solubility in Water (kg/m3) Completely soluble

Density (kg/m3) 0.850

Auto-flammability (°C) No Limits available

### 10. STABILITY AND REACTIVITY

Stability Stable when stored and used as directed.
Conditions to Avoid High temperatures and sources of ignition.

Materials to Avoid Oxidizing agents

Hazardous Decomposition Products Oxides of carbon and nitrogen smoke and toxic fumes.

Reactivity None



Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# MATERIAL SAFETY DATA SHEET BLIXEM WINDSCREEN WASHER

#### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if product is handled in accordance with this Safety Data Sheets.

Acute Effects When inhaled, may irritate the mucous membrane.

Contact to skin may result in slight irritation to sensitive skin Swallowing may result in nausea, vomiting and gut irritation.

#### 12. ECOLOGICAL INFORMATION

Mobility No information available.

Persistence/Degradability The product is expected to biodegrade very slowly with time.

and no further information is available.

#### 13. DISPOSAL

Person conducting disposal should wear appropriate PPE.

Product Disposal Dispose of in accordance with all applicable local and national

regulations.

Container Disposal An approved drum recycler can recycle containers.

#### 14. TRANSPORT INFORMATION

UN No.: 1170
Dangerous Goods Class 3
Hazchem Code 3Y
Packing Group III

## 15. REGULATORY INFORMATION

This product is not subjected to the following international agreements.

The STOCKHOLM CONVENTION
The ROTTERDAM CONVENTION
BASEL CONVENTION(Hazardous Waste)

Code letter and hazard designation of product: F – Flammable

Risk phrases: R10 Flammable.

R22 Harmful if swallowed.

Safety phrases: S02 Keep out of the reach of



Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# MATERIAL SAFETY DATA SHEET BLIXEM WINDSCREEN WASHER

S07 Keep container tightly closed.

S15 Keep away from heat.

S16 Keep away from sources of ignition.

S21 When using, do not smoke.

S25 Avoid contact with eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well ventilated areas.

#### **16. OTHER INFORMATION**

Date Of First Issue: 20 March 2020 Revision Date: 1 June 2022

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.



