

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET LUBE X ATF DX II

PRODUCT DESCRIPTION

LUBE X ATF DX II is an automatic transmission fluid for use when the manufacturer calls for a Dexron-II fluid. It is blended from virgin base oils, which have been fortified with anti-wear, antioxidant, anti-foam, anti-corrosion and viscosity index improvers together with friction modifiers. This blend of components gives high levels of performance and long service life.

PERFORMANCE STANDARDS

- GM IID
- FORD MERCON
- General Motors type A Suffix A
- Allison C-4
- Caterpillar TO-2
- ZF TE-ML 04D, 14A
- VOITH H55.6335.xx
- MAN 339 typ V1 and Z1
- MERCEDES MB-Approval 236.9
- VOLVO 97341

BENEFITS

- Gives excellent performance and long service life.
- Compatible with elastomers.
- Guards against gear wear, rust and deposit formation.
- Smooth gear change and improves power.
- All season service life.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET LUBE X ATF DX II

KEY PROPERTIES

Density @20 °C	kg/L	0.872
Viscosity @40 °C	cSt	42
Viscosity @100 °C	cSt	8
Viscosity Index		160
Pour point	°C	-45
Flash point C.O.C.	°C	200

PACKAGE SIZE	5 Litre
LUBE X ATF DX II	✓

