

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline EP 80W90 GL5

PRODUCT DESCRIPTION

High performance multipurpose extreme pressure gear lubricant for manual transmissions, transaxles, planetary hub & other spur gear axles which specifically require EP gear oils meeting API GL5.

PERFORMANCE STANDARDS

- API GL-5
- Multipurpose EP or hypoid gear oil
- MIL-2105 - D
- MAN 342 M2

BENEFITS

- High performance EP additive system controls transmission gear tooth wear.
- Excellent load carrying capacity protects gear components against surface stress under heavily loaded conditions.
- It has been fortified with anti-wear, antioxidant, anti-foam, anti-corrosion and extreme pressure additives.

KEY PROPERTIES

| | | |
|------------------|------|-------|
| Density 20 °C | kg/L | 0.890 |
| Viscosity 40 °C | cSt | 140 |
| Viscosity 100 °C | cSt | 14.2 |
| Viscosity Index | N/A | 98 |
| Pour point | °C | -30 |
| Flash point | °C | 220 |

| PACKAGE SIZE | 500 mL | 5 Litres | 20 Litres | 210 Litres |
|---------------|--------|----------|-----------|------------|
| EP 80W-90 GL5 | ✓ | ✓ | ✓ | ✓ |

