

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET FLEETLINE SAE 40 MAGNUM

### PRODUCT DESCRIPTION

Fleetline SAE 40 Magnum is a superior monograde oil that falls into the category of "Series 2" diesel automotive engine oil.

### PERFORMANCE STANDARDS

- API SF/CF4
- MIL-L-2104C
- CCMC
- ALLISON C3
- VOLVO VDS
- MB 227
- MB 228
- GM DETROIT DIESEL

### APPLICATIONS

Fleetline SAE 40 Magnum additive package controls the soot build up in equipment's that are subjected to severe load conditions and will subsequently prevents piston crown deposit and ring sticking and valve train wear.

### KEY PROPERTIES

|                   |          |      |
|-------------------|----------|------|
| SAE GRADE         |          | 40   |
| Viscosity @40 °C  | cSt      | 140  |
| Viscosity @100 °C | cSt      | 14.5 |
| Viscosity Index   | N/A      | 100  |
| Pour point        | °C       | -21  |
| TBN               | mg KOH/g | 10.5 |

| PACKAGE SIZE            | 500ml | 5 Litre |
|-------------------------|-------|---------|
| Fleetline SAE 40 Magnum | ✓     | ✓       |

