

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Lithium EP 3 Wheel Bearing

PRODUCT DESCRIPTION

Lithium EP 3 wheel bearing grease is multi-purpose lead free lithium complex grease, with excellent high temperature performance and long-life capability. Good fretting corrosion performance, low water washout and good protection against bearing corrosion, combined with excellent mechanical stability and load-carrying capability makes it ideal multipurpose grease. It consistently gives excellent high temperature performance and a wide operating temperature field from – 20°C to +150°C. EP additives increase the load carrying capacity and reduces wear.

BENEFITS

- Resistant to water wash out.
- Protects bearings against corrosion.
- Excellent lubrication properties.
- Long life.
- Economical.
- Good anti-wear properties.
- Excellent load carrying characteristics.

APPLICATIONS

This product is suitable for all grease application. It is especially suitable for grease-lubricated rolling bearings running at high speed, because of the special EP additives it is recommended in high load wheel bearing conditions at normal and high temperatures.

KEY PROPERTIES

NLGI Consistency	3
Colour	Beige
Thickener Type	Lithium/Calcium
Drop Point °C	>260
Timken OK load kg	>27



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Lithium EP 3 Wheel Bearing

Worked penetration	220-250
Base oil viscosity @ 40°C	190
Viscosity Index	98

PACKAGE SIZE	20x500g	5kg	15kg
Lith EP 3L Wheel Bearing	✓	✓	✓

